

Pressure Washer Hose & Fittings





PROJET® 4,200 PSI PRESSURE WASHER HOSE



Application:

Pressure wash equipment. All of the hose assemblies shown here are factory made with male NPT end fittings and bend restrictors at each end. One male end is a swivel to prevent hose twisting. **NOT FOR STEAM SERVICE.**

Construction:

Tube - Seamless, black synthetic rubber

Reinforcement - One braid of high-tensile steel wire

Cover - Wrapped or Smooth abrasion and weather resistant synthetic rubber, Black, Blue or Gray

Packaging - 50', 100', 150', 200' in Bulk Reels

Temperature Range:

-40°C to +121°C/149°C Intermittent (-40°F to +250°F/300°F Intermittent)

Part No.	Cover	I.D. Inches	O.D. Inches	Max W.P. PSI	Min Bend Radius	Weight lbs / ft
PJ4-06BK	Wrapped	3/8	0.59	4,200	2.6	0.15
PJ4-06GY	Wrapped	3/8	0.59	4,200	2.6	0.15
PJ4-04BLM	Smooth	1/4	0.48	4,000	2.9	0.12
PJ4-06BLM	Smooth	3/8	0.59	4,200	2.6	0.15

^{*}BK indicates the color Black. For other colors add the suffix to the part number as follows: GY - Gray, BLM - Blue (Smooth Only).

PROJET® 4,200 PSI ASSEMBLIES

Part No.	Color	Cover	Hose Size & Length	End 1	End 2	Attaching Method
PJ4-06BK-050C	Black	Wrapped	¾" x 50'	C" M-NPT Rigid	C" M-NPT Swivel	Crimp
PJ4-06BK-100C	Black	Wrapped	³⁄₃" x 100'	C" M-NPT Rigid	C" M-NPT Swivel	Crimp
PJ4-06GY-050C	Gray	Wrapped	³⁄₃" x 50'	C" M-NPT Rigid	C" M-NPT Swivel	Crimp
PJ4-06GY-100C	Gray	Wrapped	³⁄₃" x 100'	C" M-NPT Rigid	C" M-NPT Swivel	Crimp
PJ4-06BLM-050C	Blue	Smooth	³⁄₃" x 50'	C" M-NPT Rigid	C" M-NPT Swivel	Crimp
PJ4-06BLM-100C	Blue	Smooth	³⁄₃" x 100'	C" M-NPT Rigid	C" M-NPT Swivel	Crimp

^{*4,200} PSI assemblies come with Blue bend restrictors.

^{*}Call for additional fittings, lengths and assemblies.









ULTRAJET® 4,000 PSI OIL/FAT RESISTANT PRESSURE WASHER HOSE



Application:

Pressure wash equipment where maximum abrasion or oil/fat resistance is required. **NOT FOR STEAM SERVICE.**

Construction:

Tube - Seamless, black synthetic rubber

Reinforcement - One braid of high-tensile steel wire

Cover - Yellow, smooth ultra abrasion resistant synthetic rubber, ARPM Class A

Packaging - 50', 100', 150', 200' in Bulk Reels

Temperature Range:

-40°C to +121°C/149°C Intermittent (-40°F to +250°F/300°F Intermittent)

Part No.	Cover	I.D. Inches	O.D. Inches	Max W.P. PSI	Min Bend Radius	Weight lbs / ft
UJ4-06YWM	Smooth	3/8	0.61	4,000	3.5	0.24

ULTRAJET® 4,000 PSI ASSEMBLIES



Part No.	Color	Cover	Hose Size & Length	End 1	End 2	Attaching Method
UJ4-06YWM-050C	Yellow	Smooth	3∕8" x 50'	C" M-NPT Rigid	C" M-NPT Swivel	Crimp
UJ4-06YWM-100C	Yellow	Smooth	3⁄8" x 100'	C" M-NPT Rigid	C" M-NPT Swivel	Crimp

^{*4,000} PSI assemblies come with Blue bend restrictors.

^{*}Call for additional fittings, lengths and assemblies.



SUPERJET® 6,000 PSI PRESSURE WASHER HOSE



Application:

Pressure wash equipment. All of the hose assemblies shown here are factory made with male NPT end fittings and bend restrictors at each end. One male end is a swivel to prevent hose twisting. **NOT FOR STEAM SERVICE.**

Construction:

Tube - Seamless, black synthetic rubber

Reinforcement - Two braids of high-tensile steel wire

Cover - Wrapped or Smooth abrasion and weather resistant synthetic rubber, Black, Blue or Gray **Packaging** - 50', 100', 150', 200' in Bulk Reels

Temperature Range:

-40°C to +121°C/149°C Intermittent (-40°F to +250°F/300°F Intermittent)

Part No.	Cover	I.D. Inches	O.D. Inches	Max W.P. PSI	Min Bend Radius	Weight lbs / ft
SJ6-06BK	Wrapped	3/8	0.67	6,000	3.5	0.29
SJ6-06GY	Wrapped	3/8	0.67	6,000	3.5	0.29
SJ6-06BLM	Smooth	3/8	0.67	6,000	3.5	0.29

^{*}BK indicates the color Black. For other colors add the suffix to the part number as follows: GY - Gray, BLM - Blue.

SUPERJET® 6,000 PSI ASSEMBLIES

Part No.	Color	Cover	Hose Size & Length	End 1	End 2	Attaching Method
SJ6-06BK-050C	Black	Wrapped	¾" x 50'	%" M-NPT Rigid	%" M-NPT Swivel	Crimp
SJ6-06BK-100C	Black	Wrapped	¾" x 100'	¾" M-NPT Rigid	%" M-NPT Swivel	Crimp
SJ6-06GY-050C	Gray	Wrapped	¾" x 50'	¾" M-NPT Rigid	%" M-NPT Swivel	Crimp
SJ6-06GY-100C	Gray	Wrapped	¾" x 100'	¾" M-NPT Rigid	%" M-NPT Swivel	Crimp
SJ6-06BLM-050C	Blue	Smooth	¾" x 50'	¾" M-NPT Rigid	%" M-NPT Swivel	Crimp
SJ6-06BLM-100C	Blue	Smooth	¾" x 100'	¾" M-NPT Rigid	%" M-NPT Swivel	Crimp

^{*6,000} PSI assemblies come with Red bend restrictors.

^{*}Call for additional fittings, lengths and assemblies.









SUPERJET® 7,400 PSI PRESSURE WASHER HOSE



Application:

Pressure wash equipment. All of the hose assemblies shown here are factory made with male NPT end fittings and bend restrictors at each end. One male end is a swivel to prevent hose twisting. **NOT FOR STEAM SERVICE.**

Construction:

Tube - Seamless, black synthetic rubber

Reinforcement - Two braids of high-tensile steel wire

Cover - Wrapped and weather resistant synthetic rubber, Black

Packaging - 50', 100', 150', 200' in Bulk Reels

Temperature Range:

-40°C to +121°C/149°C Intermittent (-40°F to +250°F/300°F Intermittent)

ĺ	Part No.	Cover	I.D. Inches	O.D. Inches	Max W.P. PSI	Min Bend Radius	Weight lbs / ft
I	SJ7-06BK	Wrapped	3/8	0.67	7,400	3.5	0.29

SUPERJET® 7,400 PSI ASSEMBLIES



Part No.	Color	Cover	Hose Size & Length	End 1	End 2	Attaching Method
SJ7-06BK-025C	Black	Wrapped	¾" x 25'	¾" M-NPT Rigid	¾" M-NPT Rigid	Crimp
SJ7-06BK-050C	Black	Wrapped	3⁄8" x 50'	¾" M-NPT Rigid	%" M-NPT Rigid	Crimp
SJ7-06BK-075C	Black	Wrapped	3⁄8" x 75'	%" M-NPT Rigid	%" M-NPT Rigid	Crimp
SJ7-06BK-100C	Black	Wrapped	%" x 100'	%" M-NPT Rigid	%" M-NPT Rigid	Crimp
SJ7-06BK-150C	Black	Wrapped	3⁄8" x 150'	¾" M-NPT Rigid	%" M-NPT Rigid	Crimp
SJ7-06BK-200C	Black	Wrapped	3∕8" x 200'	¾" M-NPT Rigid	¾" M-NPT Rigid	Crimp

^{*7,400} PSI assemblies come with Red bend restrictors.

^{*}Call for additional fittings, lengths and assemblies.



PRESSURE WASH HOSE ACCESSORIES & FITTINGS

Pressure Washer Tips

		•
Part No.	Color	Degree
PW-N040-0RD	Red	0°
PW-N040-15YW	Yellow	15°
PW-N040-25GR	Green	25°
PW-N040-40WH	White	40°
PW-N040-65BK	Black	Std. Soaper
PW-DNZ-LR	Blue	Long Rng. Soaper



Vented Pressure Washer Lance

Part No.	Thread	Length
PW-LV036	1⁄4" M-NPT	36"



Gun Lance Alum. Assembly

Part No.	Length
PW-GLA024	24"
PW-GLA036	36"
PW-GLA048	48"



PW Wand Extension Non-Insulated w/ QDs



Part No.	Length
PW-LA012	12"
PW-LA024	24"
PW-LA036	36"
PW-LA048	48"
PW-LA072	72"
PW-LA084	84"
PW-LA096	96"
PW-LA120	120"



Pressure Washer Gun 5,000 W.P. %" in x 1/4" out

 *****	X / 4	out
Part I	No.	
PW-T	G5K	

Bend Restrictors



Size	Part No.	Color
1/4	TPG-04BK	Black
3/8	TPG-06BK	Black
3/8	TPG-06OR	Orange
3/8	TPG-06BL	Blue
3/8	TPG-06RD	Red



24" Bend Restrictor

Size	Part No.
3/8	TPG-06RD-024 (Red)
3/8	TPG-06BL-024 (Blue)



PRESSURE WASH HOSE ACCESSORIES & FITTINGS



Straight Thru Coupler Brass

Part No.	Size	Thread
QSTC44FPBR	1/4"	F-NPT
QSTC66FPBR	3/8"	F-NPT
QSTC88FPBR	1/2"	F-NPT
QSTC1212FPBR	3/4"	F-NPT



Straight Thru Plug Steel

Part No.	Size	Thread
QSTN44FP	1/4"	F-NPT
QSTN66FP	3/8"	F-NPT
QSTN88FP	1/2"	F-NPT
QSTN1212FP	3/4"	F-NPT

*Add S3 at the end of Part No. for 303 Stainless Steel.



QC Coupler Brass

Size	Part No.	Thread
1/4	QSTC44MPBR	MPT
3/8	QSTC66MPBR	MPT



QC Plug Straight Thru Brass

Size	Part No.	Thread
1/4	QSTN44MP	MPT
3/8	QSTN66MP	MPT



Straight Thru PW Coupler 303SS

Size	Part No.	Thread
1/4	QSTC44FPS3	FNPT
3/8	QSTC66FPS3	FNPT
1/2	QSTC88FPS3	FNPT
3/4	QSTC1212FPS3	FNPT



QC Plug Straight Thru 303SS

Size	Part No.	Thread
1/4	QSTN44MPS3	MPT
3/8	QSTN66MPS3	MPT



Straight Thru PW Plug 303SS

Size	Part No.	Thread
1/4	QSTN44FPS3	FNPT
3/8	QSTN66FPS3	FNPT
1/2	QSTN88FPS3	FNPT
3/4	QSTN1212FPS3	FNPT



Screw Coupler 6FP x F22

Size	Part No.	Thread
3/8	PW-FK22-6FP	FNPT



PRESSURE WASH HOSE ACCESSORIES & FITTINGS



QD Plug XM22

Size	Part No.	Thread
3/8	PW-FK22-QSTN6	FNPT



MP X F22

Size	Part No.	Thread
3/8	PW-FK22-6MP	FNPT



F22 x F22

Size	Part No.	Thread
3/8	PW-FK22-FK22	FNPT



6MP x M22

Part No.	
PW6312	



M22 x M22

Part No.	
PW-FK22-MK22	



Male Pipe 1-Piece Swivel

Size	Part No.	Thread
1/4	E04-04MPX	MNPT
3/8	E06-06MPX	MNPT



Male Pipe 1-Peice

Size	Part No.	Thread
1/4	E04-04MP	MNPT
3/8	E06-06MP	MNPT



4500 PSI PW Regulator

Part No.
PW-UNLD-4.5K



NOTES



NOTES

_



NOTES





PRESSURE WASHER HOSE & FITTINGS

CORPORATE OFFICE

50 Industrial Loop Dr N Orange Park, FL 32073 (904) 264-1267

www.hosepower.com